


PLUXO

CEILING SURFACE



1.0 LED111

LED 13W | 220-240V | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated


0.93kg IP20 $\text{S}+0.3+D$ P A 38°

45°/45° 45°/45°

	CODE
	143168W
	143168S
	143168B

Light Colour Selection

LUMEN CRI	CODE
2700K 715 >80	2
3000K 730 >80	4



2.0 LED111

2xLED 13W | 220-240V | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated


1.86kg IP20 $\text{S}+0.3+D$ P A 38°

45°/45° 45°/45°

	CODE
	143268W
	143268S
	143268B

Light Colour Selection

LUMEN CRI	CODE
2700K 2x710 >80	2
3000K 2x730 >80	4



3.0 LED111

3xLED 13W | 220-240V | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated


2.79kg IP20 $\text{S}+0.3+D$ P A 38°

45°/45° 45°/45°

	CODE
	143368W
	143368S
	143368B

Light Colour Selection

LUMEN CRI	CODE
2700K 3x710 >80	2
3000K 3x730 >80	4



4.0 LED111

4xLED 13W | 220-240V | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated

3.72kg IP20 $\text{S}+0.3+D$ P A 38°

45°/45° 45°/45°

	CODE
	143468W
	143468S
	143468B

Light Colour Selection

LUMEN CRI	CODE
2700K 4x710 >80	2
3000K 4x730 >80	4