

PRODUCT DATA SHEET

Tian Xia 500 - Led



DESIGN BY:

Carlottade Bevilacqua 2008

MATERIALS:

Polished aluminium, thermoplastic resin, translucent film, polyester

Mirror-treated finish polished aluminium structure; thermoplastic resin diffuser with translucent film mirror-finish.

Dimmer included. Tian Xia 500 Led reduces of 80% the consumption, maintaining the performances, in the sign of sustainability and as consequence to the source technology developments. Uses three systems for direct, indirect and diffused light, managed separately. By direct and indirect emissions compact fluorescent light sources are employed, while for the diffused one strips Led RGB are used, that produce 6 coloured light range and a white light.

Light emission



Diffused, direct, indirect









TECHNICAL DATA SHEET

FEATURES

Product name: Tian Xia 500 - Led A246100 Article Code:

Colour: Polished aluminium

Material: Polished aluminium, thermoplastic resin, translucent film, polyester

Series: Design **Environment:** Indoor

OPTICS

Emission: Diffused, direct, indirect

DIMENSIONS

Height: cm 29 Cutout width: cm 50 Base Diameter: cm 30 Max Height from ceiling: cm 200


Cutout shape:

LAMPS INCLUDED

LED Category: Watt: Wattage (Single): 3.4 Number: 1 x 6 Typology: 0 Class: Α

Category: **FLUO** Number: 3 Lbs: Tc-tel Watt: 42 Socket: Gx24q-4 Type: Fsm Colour Rendering: 1b

DIMENSIONS



LAMP





LUMINAIR

Starter: Electronic Integrated Voltage: 220V-240V Remote control: Infrared



Colour temperature (K): 2700 Duration (h): 10000



TELECOMANDO/CENTRALINA PARETE TOUCHA299100



ACCESSORIES



TELECOMANDO/CENTRALINA PARETE TOUCHA299100