




# DEEP IP44

CEILING RECESSED



## 1.0 LED

LED 7/10W | 350-500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.32kg | IP44 | 0.3° | 36°

87 | 90 | 4-30

	CODE
	112661W
	112661S
	112661B

### Light Colour Selection


	LUMEN   CRI	CODE
2700K	420-590   >90	3
3000K	470-640   >90	5
1800-2850K	320-440   >90	9

### ALWAYS USE

power supply

	CODE
350mA   10W	90213402
500mA   10W	90214403
500mA   15W dim	90224501

more power supplies on page 468



## 1.0 MR16

QR-CBC51 max. 35W | GU5.3  
12V | excl. transformer  
aluminium powder coated

0.26kg | IP44 | 0.9°-D

87 | 90 | 4-30

	CODE
	112610W0
	112610S0
	112610B0

### ALWAYS USE

transformer

	CODE
12V   60W	90221902
12V   105W	90221903



## 1.0 PAR16

PAR16 max. 50W | GU10  
220-240VAC | 50-60Hz  
aluminium powder coated

0.30kg | IP44 | 0.9°-D

87 | 105 | 4-30

	CODE
	112620W0
	112620S0
	112620B0

### OPTIONAL

PAR16 LED GU10 6W  
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 471