






PYRAMID

CEILING RECESSED



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.28kg IP20 3-0.3-1 36°

102x102 35°/35° 355° 90 4-30

CODE

113161W

Light Colour Selection

	LUMEN	CRI	CODE
2700K	420-590	>90	3
3000K	470-640	>90	5
1800-2850K	320-440	>90	9

ALWAYS USE

power supply

CODE

350mA 10W	90213402
500mA 10W	90214403
500mA 15W dim	90224501

more power supplies on page 468

1.0 PAR16

PAR16 max.50W | GU10
220-240VAC | 50-60Hz
aluminium powder coated

0.26kg IP20 3-0.9-1

102x102 35°/35° 355° 115 4-30

CODE

113120W0

OPTIONAL

PAR16 LED GU10 6W
phase-cut dim

CODE

2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 471

2.0 LED

2xLED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.50kg IP20 3-0.3-1 36°

102x172 35°/35° 355° 90 4-30

CODE

113261W

Light Colour Selection

	LUMEN	CRI	CODE
2700K	2x420-590	>90	3
3000K	2x470-640	>90	5
1800-2850K	2x320-440	>90	9

ALWAYS USE

power supply

CODE

350mA 10W	90213402
500mA 10W	90214403
500mA 15W dim	90224501

more power supplies on page 468

2.0 PAR16

2xPAR16 max.50W | GU10
220-240VAC | 50-60Hz
aluminium powder coated

0.46kg IP20 3-0.9-1

102x172 35°/35° 355° 115 4-30

CODE

113220W0

OPTIONAL

PAR16 LED GU10 6W
phase-cut dim

CODE

2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 471