





# DOCUS

## CEILING SUSPENDED



### 2.0 | 3.0 LED

LED 8W | 220-240VAC | 50-60Hz  
COB 2-step | incl. PS | phase-cut dim  
aluminium powder coated  
brushed

0.69 | 0.85kg IP20 36°

#### 2.0

200mm	CODE
	207564W
	207564L
	207564G
	207564P
	207564B

#### 3.0

300mm	CODE
	207664W
	207664L
	207664G
	207664P
	207664B

### Light Colour Selection

LUMEN	CRI	CODE
2700K	480   >80	2
3000K	480   >80	4
1800-2850K	410   >90	9

### 2.0 | 3.0 PAR16

PAR16 max.35W | GU10  
220-240VAC | 50-60Hz  
aluminium powder coated  
brushed

0.62 | 0.75kg IP20 36°

#### 2.0

200mm	CODE
	207520W0
	207520L0
	207520G0
	207520P0
	207520B0

#### 3.0

300mm	CODE
	207620W0
	207620L0
	207620G0
	207620P0
	207620B0

### OPTIONAL

PAR16 LED GU10 6W  
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 471