



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.34kg IP20 3-0.3-D 36°

102 35°/35° 355° 90 4-40

	CODE
	110161W_
	110161S_
	110161B_

blade springs

	CODE
	110161W_C

Light Colour Selection


	LUMEN CRI	CODE
2700K	420-590 >90	3
3000K	470-640 >90	5
1800-2850K	320-440 >90	9

ALWAYS USE

power supply

	CODE
350mA 10W	90213402
500mA 10W	90214403
500mA 15W dim	90224501

more power supplies on page 468



1.0 MR16

QR-CBC51 max.50W | GU5.3
12V | excl. transformer
aluminium powder coated

0.28kg IP20 3-0.9-D

102 35°/35° 355° 75 4-40

	CODE
	110110W0
	110110S0
	110110B0



blade springs

	CODE
	110110W0C

ALWAYS USE

transformer

	CODE
12V 60W	90221902
12V 105W	90221903



1.0 PAR16

PAR16 max.50W | GU10
220-240VAC | 50-60Hz
aluminium powder coated

0.32kg IP20 3-0.9-D

102 35°/35° 355° 100 4-40

	CODE
	110120W0
	110120S0
	110120B0

blade springs

	CODE
	110120W0C

OPTIONAL

PAR16 LED GU10 6W
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 471