



### 1.0 LED

LED 7/10W | 350-500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.25kg IP20 35°/35° 355° 100 4-30

87 35°/35° 355° 100 4-30

|         | CODE    |
|---------|---------|
| 112461W | 112461W |
| 112461S | 112461S |
| 112461G | 112461G |
| 112461B | 112461B |

#### Light Colour Selection

|            | LUMEN   CRI   | CODE |
|------------|---------------|------|
| 2700K      | 420-590   >90 | 3    |
| 3000K      | 470-640   >90 | 5    |
| 1800-2850K | 320-440   >90 | 9    |

### ALWAYS USE

power supply

|                 | CODE     |
|-----------------|----------|
| 350mA   10W     | 90213402 |
| 500mA   10W     | 90214403 |
| 500mA   15W dim | 90224501 |

more power supplies on page 468



### 1.0 MR16

QR-CBC51 max.50W | GU5.3  
12V | excl. transformer  
aluminium powder coated

0.19kg IP20 35°/35° 355° 90 4-30

87 35°/35° 355° 90 4-30

|          | CODE     |
|----------|----------|
| 112410W0 | 112410W0 |
| 112410S0 | 112410S0 |
| 112410G0 | 112410G0 |
| 112410B0 | 112410B0 |

### ALWAYS USE

transformer

|            | CODE     |
|------------|----------|
| 12V   60W  | 90221902 |
| 12V   105W | 90221903 |



### 1.0 PAR16

PAR16 max.50W | GU10  
220-240VAC | 50-60Hz  
aluminium powder coated

0.23kg IP20 35°/35° 355° 115 4-30

87 35°/35° 355° 115 4-30

|          | CODE     |
|----------|----------|
| 112420W0 | 112420W0 |
| 112420S0 | 112420S0 |
| 112420G0 | 112420G0 |
| 112420B0 | 112420B0 |

### OPTIONAL

PAR16 LED GU10 6W  
phase-cut dim

|            | CODE     |
|------------|----------|
| 2700K      | 901228W2 |
| 3000K      | 901228W4 |
| 1800-2850K | 901229S9 |

more lamps and specs on page 471